

IP 话机 MP100 参考设计

IP



MP100

IP



uContact MP100

IP

SIP

SIP

IP-PBX

IMS

MP100

Juphoon[®] SIP
Stack IMS (IMS
Client Platform)

CPU

IMS

400MHz

Analog Devices Blackfin[®]
BF531

MP100

SIP

IMS

LCD

BF53

LCD

GIPS[®]



- ID
- &
- &
- / / /
- /
-
-
-
- DTMF (Inbound / Outbound / SIP-Info)
- (, &)
- (LCD &)
- &
- Session Timer
-
-
- (&)
- SIP
- Syslog , Telnet, Ping & Trace route
-
-
-
- G.711u / a G.729ab G.723.1a
-
-
- x x 108 mm x 210 mm x 185 mm
- AC 100~240V, 50-60Hz, DC
- 5V, 1.2A
- IEEE 802.3 10/100 Base-T
- 1.8W ~ 2.1W
-
- 64*128 LCD
-
- 10/100 Base-T
-
- XML profile
- SIP RFC3261 RFC
- DNS (A SRV NAPTR)
- STUN
- SNMP v2 TR069
- HTTP TFTP
- / DHCP / PPPoE
- NTP / Register
- XML
- IEEE802.1p / Q tagging (VLAN)
- /
- NAT Keep Alive
- 3 DSCP
- ZTE Soft-switch and IMS Server
- Ericsson IMS Server
- Nokia IMS Server
- Asterisk SIP Server
- SER SIP Server
-

+86-574-87287820
 +86-574-87304379
 www.juphoon.com